

# ETFE RTD WIRE UNSHIELDED

## PRODUCT DESCRIPTION

<b>Conductor</b>	Stranded
<b>AWG Sizes</b>	#16 AWG - #26 AWG
<b>Insulation / Jacket Type</b>	(ETFE ) 150C
<b>Color Code</b>	2C (Red / White) / 3C (Red/Red/White) 4C (Red/Red/White/White)
<b>Conductor Material</b>	Silver Plated Copper
<b>Shield Type</b>	Unshielded / Twisted
<b>Approvals</b>	Rohs / Reach Compliant
<b>Applications</b>	Resistance Temperature Detectors / Thermometers / Sensors
<b>Physical Properties</b>	Excellent resistance to abrasion, gasoline, oil, moisture and acid

Part#	Conductor	Insulation Thickness	Overall Diameter *	Weight lbs/k ft	Temp Rating	Voltage
R1692UZ	2c - 16/19	.006"	.150"	20.6	150C	n/a
R1693UZ	3c - 16/19	.006"	.160"	29.5	150C	n/a
R1694UZ	4c - 16/19	.006"	.177"	38.5	150C	n/a
R1892UZ	2c - 18/19	.006"	.138"	16.4	150C	n/a
R1893UZ	3c - 18/19	.006"	.147"	23.3	150C	n/a
R1894UZ	4c - 18/19	.006"	.162"	30.3	150C	n/a
R2072UZ	2c - 20/7	.006"	.120"	11.4	150C	n/a
R2073UZ	3c - 20/7	.006"	.128"	16.0	150C	n/a
R2074UZ	4c - 20/7	.006"	.141"	20.8	150C	n/a
R2272UZ	2c - 22/7	.006"	.104"	7.8	150C	n/a
R2273UZ	3c - 22/7	.006"	.110"	10.8	150C	n/a
R2274UZ	4c - 22/7	.006"	.121"	13.8	150C	n/a
R2472UZ	2c - 24/7	.006"	.092"	5.6	150C	n/a
R2473UZ	3c - 24/7	.006"	.097"	7.6	150C	n/a
R2474UZ	4c - 24/7	.006"	.107"	9.7	150C	n/a
R2672UZ	2c - 26/7	.006"	.082"	4.1	150C	n/a
R2673UZ	3c - 26/7	.006"	.087"	5.4	150C	n/a
R2674UZ	4c - 26/7	.006"	.095"	6.8	150C	n/a