

# PFA RTD WIRE UNSHIELDED

## PRODUCT DESCRIPTION

<b>Conductor</b>	Stranded
<b>AWG Sizes</b>	#16 AWG - #26 AWG
<b>Insulation / Jacket Type</b>	(PFA) 260C
<b>Color Code</b>	2C (Red / White) / 3C (Red/Red/White) 4C (Red/Red/White/White)
<b>Conductor Material</b>	Nickel Plated Copper
<b>Shield Type</b>	Unshielded / Twisted
<b>Approvals</b>	Rohs / Reach Compliant
<b>Applications</b>	Resistance Temperature Detectors / Thermometers / Sensors
<b>Physical Properties</b>	Excellent resistance to abrasion, oil, moisture , acid and low smoke

Part#	# Conductor AWG	Insulation Thickness	Overall Diameter *	Weight lbs/k ft	Temp Rating	Voltage
R1692U2P	2c - 16/19	.006"	.150"	21.8	260C	n/a
R1693U2P	3c - 16/19	.006"	.160"	31.0	260C	n/a
R1694U2P	4c - 16/19	.006"	.177"	40.3	260C	n/a
R1892U2P	2c - 18/19	.006"	.138"	17.5	260C	n/a
R1893U2P	3c - 18/19	.006"	.147"	24.7	260C	n/a
R1894U2P	4c - 18/19	.006"	.162"	32.0	260C	n/a
R2072U2P	2c - 20/7	.006"	.120"	12.3	260C	n/a
R2073U2P	3c - 20/7	.006"	.128"	17.1	260C	n/a
R2074U2P	4c - 20/7	.006"	.141"	22.1	260C	n/a
R2272U2P	2c - 22/7	.006"	.104"	8.5	260C	n/a
R2273U2P	3c - 22/7	.006"	.110"	11.7	260C	n/a
R2274U2P	4c - 22/7	.006"	.121"	14.9	260C	n/a
R2472U2P	2c - 24/7	.006"	.092"	6.3	260C	n/a
R2473U2P	3c - 24/7	.006"	.097"	8.4	260C	n/a
R2474U2P	4c - 24/7	.006"	.107"	10.6	260C	n/a
R2672U2P	2c - 26/7	.006"	.082"	4.6	260C	n/a
R2673U2P	3c - 26/7	.006"	.087"	6.1	260C	n/a
R2674U2P	4c - 26/7	.006"	.095"	7.6	260C	n/a